



TECHNICAL DATA SHEET

Neville Chemical Company
2800 Neville Road
Pittsburgh, PA 15225-1496

Phone: 412-777-4210
E-Mail: support@nevchem.com
Internet: www.nevchem.com

LX-1000[®]-130

PRODUCT DESCRIPTION

LX-1000[®]-130 is a thermoplastic low molecular weight hydrocarbon resin produced by thermal polymerization of mixed DCPD and aromatic monomers derived from petroleum feedstocks.

APPLICATIONS / END USES

- Mastics, Construction and Flooring Adhesives
- High Solids Solvent Borne Alkyd Based Coatings
- Litho Printing Inks
- Tire and Industrial Rubber Products

ATTRIBUTES / BENEFITS

- Enhanced Wetting of Pigments and Fillers
- Compatible with Long and Medium Oil Alkyds
- Improves Tack and Bond Strength in Adhesives
- Soluble in Aliphatic and Aromatic Solvents, Naphthenic, Soya and Linseed Oils
- Low Molecular Weight
- Low VOC
- Hydrophobic—Improves moisture Resistance

PROPERTIES

Property	Test Method	Typical Value	Specifications
Softening Point, R&B °C	ASTM E28	130	130 ± 5
Gardner Color (50% in 100 Solvent)	ASTM D1544	12	15 Max.
Specific Gravity @ 25°C	ASTM D71	1.10	NA
Brookfield Viscosity , cps. @ 160°C @ 180°C @ 200°C	ASTM 3236	16,400 2,260 550	NA
Molecular Weight Mn Mw	ASTM D5296	410 900	NA
Appearance	Visual	Amber Color Flakes	NA

PACKAGING

LX-1000-130 is packaged in 50 lb. (22.7/kg.) bags or super sacks

Neville Chemical Company certifies that all components of this product are on the TSCA Inventory.