



# TECHNICAL DATA SHEET

Neville Chemical Company  
2800 Neville Road  
Pittsburgh, PA 15225-1496

Phone: 412-777-4210  
E-Mail: support@nevchem.com  
Internet: www.nevchem.com

LX<sup>®</sup>-2250

## PRODUCT DESCRIPTION

LX<sup>®</sup>-2250 is a low molecular weight, maleated liquid hydrocarbon resin/vegetable oil hybrid produced by thermal polymerization of DCPD and natural derived feedstocks.

## APPLICATIONS / END USES

- Litho Printing Inks:  
Dry Grind Dispersions  
Flushed Colors  
Finished Inks

## ATTRIBUTES / BENEFITS

- Enhanced Wetting of Pigments
- Induces Flow
- Improves Ink transferability

## PROPERTIES

Property	Test Method	Typical Value	Specifications
Gardner Viscosity @ 25°C, bbs.	ASTM D1545	35	35 ± 15
Gardner Color, Straight	ASTM D1544	8	10 Max.
Acid Number	Neville 12.18.80	18	18 ± 3
Specific Gravity @ 100°F	ASTM D71	0.98	NA
VOC, %	Neville 11.34	<0.5	NA
Appearance	Visual	Yellow Liquid	NA

## PACKAGING

LX-2250 Resin is shipped in drums, 400 pounds net weight and bulk

Neville Chemical Company certifies that all components of this product are on the TSCA Inventory.