



TECHNICAL DATA SHEET

Neville Chemical Company
2800 Neville Road
Pittsburgh, PA 15225-1496

Phone: 412-777-4210
E-Mail: support@nevchem.com
Internet: www.nevchem.com

LX[®]-3843 Resin

PRODUCT DESCRIPTION

LX[®]-3843 is a low molecular weight, liquid tackifying hydrocarbon resin produced by thermal polymerization of mixed DCPD, aromatic and alicyclic monomers derived from petroleum feedstocks

APPLICATIONS / END USES

- Interior Wood Stains - Pigmented and Clear
- Core Oil for Foundries

ATTRIBUTES / BENEFITS

- Excellent Pigment Wetting and Dispersion
- Enhances Natural Wood Grain
- Promotes Water Beading and Minimized Water Marking on Stained Wood.
- Allows Stain to Penetrate Deeply into Wood.

PROPERTIES

Property	Test Method	Typical Value	Specifications
GH Viscosity @25°C., bbs.	ASTM D1545	25	20 - 27
Gardner Color (Straight)	ASTM D1544	11	14 Max.
Iodine Number	ASTM D1959	130	NA
Specific Gravity @ 30°C	ASTM D891	0.99	NA
Flash Point, °F (TCC)	ASTM D56	105	NA
Non-Volatiles, Wt.%	Neville 11.18	70	NA
Appearance	Visual	Yellow Liquid	NA

PACKAGING: LX-3843 is packaged in 400 pound drums or bulk.

Neville Chemical Company certifies that all components of this product are on the TSCA Inventory.