



TECHNICAL DATA SHEET

Neville Chemical Company
2800 Neville Road
Pittsburgh, PA 15225-1496

Phone: 412-777-4210
E-Mail: support@nevchem.com
Internet: www.nevchem.com

NEVCHEM[®] 240

PRODUCT DESCRIPTION

NEVCHEM[®] 240 is a thermoplastic low molecular weight, C9 hydrocarbon resin produced by catalytic polymerization of mixed aromatic monomers derived from petroleum feedstocks.

APPLICATIONS / END USES

- End Block Modifier for SBC Based Adhesives
- Adhesives and Sealants
- Solvent Based Adhesives
- Building and Construction Adhesives
- High Solids Solvent-Borne and Epoxy Based Coatings
- Asphalt Modification

ATTRIBUTES / BENEFITS

- Excellent compatibility with a Broad Range of Polymers and Elastomers
- Increases Cohesive Strength in SBC Based Adhesives
- Compatible with Medium and Long Oil Alkyls
- Enhances Wetting of Pigments and Fillers
- Improves Resistance to Acids and Alkalis
- Provides Excellent Leafing Characteristics for Metallic Pigments
- Improves Gloss
- Hydrophobic-Improved Moisture Resistance
- Fast Dry
- Good Thermal Stability
- Increases Film Hardness
- Low Molecular Weight

PROPERTIES

Property	Test Method	Typical Value	Specifications
Softening Point, R&B °C	ASTM E28	136	140 ± 5
Gardner Color (50% in 100 Solvent)	ASTM D1544	7	10 max.
Specific Gravity @ 25°C	ASTM D71	1.08	NA
Brookfield Viscosity, cps @ 200°C @ 220°C	ASTM 3236	750 235	NA
Molecular Weight Mn Mw	ASTM D5296	770 1,650	NA
Appearance	Visual	Light Yellow	NA

PACKAGING

NEVCHEM[®] 240 Resin is shipped 50 lb. (22.7 kg.) bags or super sacks.

Neville Chemical Company certifies that all components of this product are on the TSCA Inventory.