



TECHNICAL DATA SHEET

Neville Chemical Company
2800 Neville Road
Pittsburgh, PA 15225-1496

Phone: 412-777-4210
E-Mail: support@nevchem.com
Internet: www.nevchem.com

NEVOXY[®] EPX-L2

PRODUCT DESCRIPTION

NEVOXY[®] EPX-L2 is a low molecular weight, methyl styrenated phenol liquid hydrocarbon resin produced by catalytic polymerization of petroleum derived feedstocks.

APPLICATIONS / END USES

- Epoxy, Urethane and Acrylic Coatings
- Protective and Marine Coatings
- Industrial Maintenance Coatings
- Epoxy Floor Coatings
- Tint Colorants
- Substitute for Benzyl Alcohol
- Epoxy Based Concrete Primer Sealants

ATTRIBUTES / BENEFITS

- Reduces Viscosity
- Improves Adhesion and Intercoat Adhesion
- Enhances Flow and Leveling
- Moderates "Pot Life"
- Extends "Recoat" Window
- Excellent UV Stability
- Improves Pigment Wetting and Dispersion
- Light Color
- Low Odor and Low VOC's
- Improved Flexibility

PROPERTIES

Property	Test Method	Typical Value	Specifications
Brookfield Viscosity, cps @ 25°C	ASTM D2196-86	130	175 ± 75
Gardner Color, Straight	ASTM D1544	1	3 Max
Specific Gravity @ 25°C	ASTM D891	1.00	N/A
Hydroxyl Number	ASTM E222	50	N/A
Molecular Weight, GPC Mn Mw	ASTM D5296	230 250	N/A
Appearance	Visual	Light Yellow Liquid	N/A

PACKAGING: NEVOXY EPX-L2 Resin is shipped in 440 lb. net weight drums.

TSCA Status: Neville Chemical Company certifies that all components of this product are on the TSCA Inventory.