

Safety Data Sheet

Material Name: Hydrocarbon Resin
NEVPENE® 9545 Resin



Section 1 – PRODUCT IDENTIFICATION

Material Name:
Hydrocarbon Resin

Trade Name:
NEVPENE® 9545 Resin

Recommended Uses of Product and Restrictions

Identified Uses: Adhesives, coatings, rubber
Uses Advised Against: None Known

Manufacturer Information

Neville Chemical Company
2800 Neville Road
Pittsburgh, PA 15225-1496
Phone:412-331-4200
Emergency Phone #: 412-331-4200 or CHEMTREC at 800-424-9300
Fax:412-777-4234

Section 2 - HAZARD(S) IDENTIFICATION

Classification in accordance with 29 CFR 1910.1200

No classification is assigned based on classification criteria.

GHS LABEL ELEMENTS

Symbol(s)
None needed according to classification criteria.

Signal Word
WARNING

Hazard Statement(s)
None

Precautionary Statement(s)

Prevention
None needed according to classification criteria.

Response
None needed according to classification criteria.

Safety Data Sheet

Material Name: Hydrocarbon Resin
NEVPENE® 9545 Resin

Storage

None needed according to classification criteria.

Disposal

Dispose in accordance with all applicable regulations.

Hazard(s) Not Otherwise Classified

Contact with molten (hot) material may cause thermal burns.

Section 3 - COMPOSITION / INFORMATION ON INGREDIENTS

CAS	Component	Percentage
68131-89-5	Petroleum Hydrocarbon Resin	Proprietary
64742-52-5	Distillates, petroleum, hydrotreated heavy naphthenic	Proprietary

Naphthalene is a non-reactive component that may be present in some of the raw materials used to produce hydrocarbon resins. It is removed from our finished product during the distillation phase of our process but may be present in trace amounts

Section 4 - FIRST-AID MEASURES

Description of Necessary Measures

Inhalation

If adverse effects occur, remove to uncontaminated area. Give artificial respiration if not breathing. Get immediate medical attention.

Skin Contact

Wash skin with soap and water for at least 15 minutes while removing contaminated clothing and shoes. Get immediate medical attention, if needed. Thoroughly clean and dry contaminated clothing before reuse.

Eye Contact

Flush eyes with plenty of water for at least 15 minutes. Then get immediate medical attention.

Ingestion

If swallowed, get medical attention. Do NOT induce vomiting.

Safety Data Sheet

Material Name: Hydrocarbon Resin
NEVPENE® 9545 Resin

Most Important Symptoms/Effects

Acute

Mild skin irritation.

Delayed

No information on significant adverse effects.

Indication of Immediate Medical Attention and Special Treatment Needed, If Needed

Provide general supportive measures and treat symptomatically.

* * *Section 5 - FIRE-FIGHTING MEASURES* * *

Suitable Extinguishing Media

Dry chemical, carbon dioxide, foam, water spray

Unsuitable Extinguishing Media

Do not use high-pressure water streams.

Special Hazard Arising from the Chemical

Avoid generating vapors; vapors dispersed in air in sufficient concentrations, and in the presence of an ignition source is a potential explosion hazard. Vapors are heavier than air and can collect in low areas; vapors can travel to an ignition source and flash back

Combustion: Upon combustion, this product emits carbon monoxide, carbon dioxide and/or low molecular weight hydrocarbons.

Fire Fighting Measures

Keep away from sources of ignition. Avoid inhalation of material or combustion by-products. Move material from fire area if it can be done without risk. Use extinguishing agents appropriate for surrounding fire. Dike for later disposal. Stay upwind and keep out of low areas.

Special Protective Equipment and Precautions for Firefighters

Wear full protective fire fighting gear including self contained breathing apparatus (SCBA) for protection against possible exposure.

Safety Data Sheet

Material Name: Hydrocarbon Resin
NEVPENE® 9545 Resin

Section 6 - ACCIDENTAL RELEASE MEASURES

Personal Precautions, Protective Equipment and Emergency Procedures

Wear appropriate personal protective equipment. Keep unnecessary people away, isolate hazard area and deny entry. Avoid contact with skin and eyes. Avoid release to the environment. Only personnel trained for the hazards of this material should perform clean up and disposal.

Methods and Materials for Containment and Cleaning Up

Use non-sparking tools and equipment. Keep unnecessary people away, isolate hazard area and deny entry. Absorb with sand or other non-combustible material. Keep out of water supplies, sewers and soil. Collect spilled material in appropriate container for disposal. In case of spillage, stop the flow of material and block any potential routes to water systems.

Section 7 - HANDLING AND STORAGE

Precautions for Safe Handling

Keep away from heat, sparks, open flame, and hot surfaces - No smoking. Wear protective gloves and eye/face protection. Keep away from all ignition sources. Avoid contact with skin and eyes. Always wear recommended personal protective equipment. Wear personal protective clothing and equipment, see Section 8. Take precautionary measures against static discharge. Dissipate static electricity during transfer by earthing (grounding and bonding) containers and equipment. Do not breathe vapor or mist.

Conditions for Safe Storage, including any Incompatibilities

Store in a cool, dry place. Store in a well-ventilated area. Avoid contact with molten (hot) material. Keep separated from incompatible substances. Keep container tightly closed. Empty containers may contain product residue. Do not reuse empty containers without commercial cleaning or reconditioning. Store and handle in accordance with all current regulations and standards.

Incompatibilities: strong oxidizing materials, combustible materials

Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

Component Exposure Limits

None

Safety Data Sheet

Material Name: Hydrocarbon Resin
NEVPENE® 9545 Resin

Appropriate Engineering Controls

Provide a local exhaust ventilation system. Ventilation equipment should be explosion-resistant if explosive concentrations of material are present. It is recommended that all vapor control equipment such as local exhaust ventilation and material transport systems involved in handling of these product contain explosion relief vents or an explosion suppression system or an oxygen-deficient environment. Ensure that vapor-handling systems (such as exhaust ducts, vessels, and processing equipment) are designed in a manner to prevent the escape of vapors into the work area (i.e., there is no leakage from the equipment). Use only appropriately classified electrical equipment and powered industrial trucks.

Individual Protection Measures, such as Personal Protective Equipment

Eyes/Face Protection

Wear splash resistant safety goggles with a face shield.

Skin Protection

Wear appropriate chemical resistant clothing.

Glove Recommendations

Wear appropriate chemical resistant gloves.

Respiratory Protection

A NIOSH approved respirator with organic vapor cartridges and N95 filters may be permissible under certain circumstances where airborne concentrations are expected to exceed exposure limits, or when symptoms have been observed that are indicative of overexposure.

* * *Section 9 - PHYSICAL AND CHEMICAL PROPERTIES* * *

Physical State:	Viscous Liquid	Vapor Density (air = 1):	>1
Appearance/ Color:	Amber	Evaporation Rate (water=1):	<1
Odor:	petroleum odor	pH:	Not available
Odor Threshold:	Not available	Boiling Point:	>230°C
R&B Softening Point, °C.:	Not available	Boiling Point Range:	Not Available
Melting Point:	Not available	Decomposition Temperature:	Not available
Freezing Point:	Not available	KOC:	Not available
Specific Gravity (water = 1):	Approx. 0.97 @ 25°C	Log KOW:	Not available
Molecular Weight (Mn):	350	Water Solubility:	Not available
(Mw):	950	Coeff. Water/Oil Dist:	Not available
VOC:	Not available	Relative Density:	Not available
Flash Point:	≈400 °F	Brookfield Viscosity:	45,000 ± 15,000 cps. @ 25°C.
OSHA Flammability Class:	Combustible Liquid	Taste:	Not available
Minimum Explosive Concentration:	10 – 20 g/m3	LEL:	Not available
KSt-value (bar x m/s):	Not available	UEL:	Not available
Auto Ignition Temperature:	> 270°C		

Safety Data Sheet

Material Name: Hydrocarbon Resin
NEVPENE® 9545 Resin

Section 10 - STABILITY AND REACTIVITY

Reactivity

None known.

Chemical Stability

Stable at normal temperatures and pressure.

Possibility of Hazardous Reactions

Hazardous polymerization will not occur.

Conditions to Avoid

Avoid heat, flames, sparks and other sources of ignition. Avoid contact with incompatible materials. Avoid generating dust. Avoid contact with molten material.

Incompatible Materials

strong oxidizing materials

Hazardous Decomposition Products

Upon decomposition, this product emits carbon monoxide, carbon dioxide and/or low molecular weight hydrocarbons.

Combustion: oxides of carbon, carbon monoxide, hydrocarbons.

Section 11 - TOXICOLOGICAL INFORMATION

Acute and Chronic Toxicity

Component Analysis - LD50/LC50

The components of this material have been reviewed in various sources and the following selected endpoints are published: None

Information on Likely Routes of Exposure

Inhalation

May cause drowsiness and dizziness May cause respiratory irritation

Ingestion

No information on significant adverse effects.

Safety Data Sheet

Material Name: Hydrocarbon Resin
NEVPENE® 9545 Resin

Skin Contact

May cause damage to skin through prolonged or repeated exposure.

Eye Contact

No information on significant adverse effects.

Immediate Effects

Mild skin irritation

Delayed Effects

May cause damage to skin through prolonged or repeated exposure.

Medical Conditions Aggravated by Exposure

No data available.

Irritation/Corrosivity Data

No information available for the product.

Respiratory Sensitization

No information available for the product.

Dermal Sensitization

No information available for the product.

Germ Cell Mutagenicity

No information available for product.

Carcinogenicity

Component Carcinogenicity

CAS # 64742-52-5	Distillates, petroleum, hydrotreated heavy naphthenic
ACGIH:	A2 – Suspected Human Carcinogen (related to Untreated and mildly treated oils)
IARC:	Monograph 100F [2012]; Supplement 7 [1987]; Monograph 33 [1984] (related to Untreated and mildly-treated oils) (Group 1 (carcinogenic to humans))
OSHA:	Present (related to Untreated and mildly-treated oils)
Comments:	This material is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA. Meets EU requirement of less than 3% (w/w) DMSO extract for total polycyclic aromatic compound (PAC) using IP 346.

Safety Data Sheet

Material Name: Hydrocarbon Resin
NEVPENE® 9545 Resin

Reproductive Toxicity

No information available for product.

Specific Target Organ Toxicity - Single Exposure

No information available for the product.

Specific Target Organ Toxicity - Repeated Exposure

No information available for the product.

Aspiration Hazard

No information available for the product.

Section 12 - ECOLOGICAL INFORMATION
--

Ecotoxicity

No information available for the product

Component Analysis - Aquatic Toxicity

CAS # 64742-52-5	Distillates, petroleum, hydrotreated heavy naphthenic
Fish:	LC50 96 h Oncorhynchus mykiss >5000 mg/L
Invertebrate:	EC50 48 h Daphnia magna >1000 mg/L IUCLID

Persistence and Degradability

No information available for the product.

Bioaccumulation

No information available for the product. May have the potential to bioaccumulate

Mobility in Soil

No information available for the product.

Other Adverse Effects:

No information available for this product

Safety Data Sheet

Material Name: Hydrocarbon Resin
NEVPENE® 9545 Resin

Section 13 - DISPOSAL CONSIDERATIONS

Disposal Methods

Dispose in accordance with all applicable regulations. Regulations vary. Consult local authorities before disposal.

Disposal of Contaminated Packaging

Dispose of waste material according to Local, State, Federal, and Provincial Environmental Regulations.

Section 14 - TRANSPORT INFORMATION

US DOT Information

Shipping Name: Elevated temperature liquid, n.o.s. at or above 100 °C and below its flash point including molten metals, molten salts, etc. (Contains: Naphtha (petroleum), aromatic-containing)

UN/NA #: 3257 Hazard Class: 9 Packing Group: III

Required Label(s): 9

Not regulated in Non-Bulk Packaging (Drums / Pails).

TDG Information

Shipping Name: Elevated temperature liquid, n.o.s. at or above 100 °C and below its flash point including molten metals, molten salts, etc. (Contains: Naphtha (petroleum), aromatic-containing)

UN #: 3257 Hazard Class: 9 Packing Group: III

Required Label(s): 9

Section 15 - REGULATORY INFORMATION

U.S. Federal Regulations

This material does not contain any chemicals required to be identified under SARA Section 302 (40 CFR 355 Appendix A), SARA Section 313 (40 CFR 372.65), CERCLA (40 CFR 302.4), TSCA 12(b), and/or require an OSHA process safety plan.

SARA Section 311/312 (40 CFR 370 Subparts B and C)

Acute Health: No, Chronic Health: No, Fire: No, Pressure: No, Reactive: No

Safety Data Sheet

Material Name: Hydrocarbon Resin
NEVPENE® 9545 Resin

U.S. State Regulations

The following components appear on one or more of the following state hazardous substances lists:

Component	CAS	CA	MA	MN	NJ	PA
Distillates, petroleum, hydrotreated heavy naphthenic	64742-52-5	No	No	No	No	No
Distillates, petroleum, hydrotreated light naphthenic	64742-53-6	No	Yes	No	No	No

Not regulated under California Proposition 65

Canada Regulations

This product has been classified in accordance with the criteria of the Controlled Products Regulations (CPR) and the SDS contains all of the information required by the CPR.

Canadian WHMIS Ingredient Disclosure List (IDL)

None of the components of this material is on Canadian WHMIS Ingredient Disclosure List.

Canadian WHMIS Information

Not classified

Component Analysis – Inventory

Component	CAS	US	CA	EU	AU	PH	JP	KR	CN	NZ
Petroleum Hydrocarbon Resin	68410-16-2	Yes	DSL	Exmt	Yes	No	Yes [^]	Yes	No	Yes
Distillates, petroleum, hydrotreated heavy naphthenic	64742-52-5	Yes	DSL	EIN #1	Yes	Yes	No	Yes	Yes	Yes
Distillates, petroleum, hydrotreated light naphthenic	64742-53-6	Yes	DSL	EIN #2	Yes	Yes	No	Yes	Yes	Yes

Exmt: Exempt Polymer

#1) List of registered substances. RLN EC No.: 265-155-0

#2) List of registered substances. RLN EC No.: 265-156-6

[^] Yes per alternate description using CAS # 64742-16-1 Petroleum Resin

Safety Data Sheet

Material Name: Hydrocarbon Resin
NEVPENE® 9545 Resin

Section 16 - OTHER INFORMATION

NFPA Ratings: Health: 1 Fire: 1 Reactivity: 0

Hazard Scale: 0 = Minimal 1 = Slight 2 = Moderate 3 = Serious 4 = Severe

HMIS RATINGS:

Health: 1

Fire: 1

Reactivity: 0

Pers. Prot.: B Minimum

Hazard Scale: 0 = Minimal 1 = Slight 2 = Moderate 3 = Serious 4 = Severe * = Chronic hazard

Key / Legend

ACGIH - American Conference of Governmental Industrial Hygienists; ADR - European Road Transport; AU - Australia; BOD - Biochemical Oxygen Demand; C - Celsius; CA - Canada; CAS - Chemical Abstracts Service; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CN - China; CPR - Controlled Products Regulations; DFG - Deutsche Forschungsgemeinschaft; DOT - Department of Transportation; DSL - Domestic Substances List; EEC - European Economic Community; EINECS - European Inventory of Existing Commercial Chemical Substances; EPA - Environmental Protection Agency; EU - European Union; F - Fahrenheit; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; ICAO - International Civil Aviation Organization; IDL - Ingredient Disclosure List; IMDG - International Maritime Dangerous Goods; JP - Japan; Kow - Octanol/water partition coefficient; KR - Korea; LEL - Lower Explosive Limit; LOLI - List Of Lists™ - ChemADVISOR's Regulatory Database; MAK - Maximum Concentration Value in the Workplace; MEL - Maximum Exposure Limits; NFPA - National Fire Protection Agency; NIOSH - National Institute for Occupational Safety and Health; NJTSR - New Jersey Trade Secret Registry; NTP - National Toxicology Program; NZ - New Zealand; OSHA - Occupational Safety and Health Administration; PH - Philippines; RCRA - Resource Conservation and Recovery Act; RID - European Rail Transport; RTECS - Registry of Toxic Effects of Chemical Substances®; SARA - Superfund Amendments and Reauthorization Act; STEL - Short-term Exposure Limit; TDG - Transportation of Dangerous Goods; TSCA - Toxic Substances Control Act; TWA - Time Weighted Average; UEL - Upper Explosive Limit; US - United States

Other Information

Reasonable care has been taken in the preparation of this information; however, the manufacturer makes no warranty whatsoever including the warranty of merchantability, expressed or implied, with respect to this information.