

# Safety Data Sheet

Material Name: Hydrocarbon Resin  
NEVTAC® LT Resin



## \*\*\*Section 1 – PRODUCT IDENTIFICATION\*\*\*

**Material Name:**  
Hydrocarbon Resin

**Trade Name:**  
NEVTAC® LT Resin

### **Recommended Uses of Product and Restrictions**

Identified Uses: Adhesives, coatings, rubber  
Uses Advised Against: None Known

### **Manufacturer Information**

Neville Chemical Company  
2800 Neville Road  
Pittsburgh, PA 15225-1496  
Phone: 412-331-4200  
Emergency Phone #: 412-331-4200 or CHEMTREC at 800-424-9300  
Fax: 412-777-4234

## \*\*\*Section 2 - HAZARD(S) IDENTIFICATION\*\*\*

### **Classification in accordance with 29 CFR 1910.1200.**

No classification is assigned based on classification criteria.

### **GHS LABEL ELEMENTS**

#### **Symbol(s)**

None needed according to classification criteria.

#### **Signal Word**

None

#### **Hazard Statement(s)**

None

#### **Precautionary Statement(s)**

#### **Prevention**

None needed according to classification criteria.

#### **Response**

None needed according to classification criteria.

# Safety Data Sheet

Material Name: Hydrocarbon Resin  
NEVTAC® LT Resin

## Storage

None needed according to classification criteria.

## Disposal

Dispose in accordance with all applicable regulations.

## Hazard(s) Not Otherwise Classified

Contact with molten (hot) material may cause thermal burns.

### \*\*\*Section 3 - COMPOSITION / INFORMATION ON INGREDIENTS\*\*\*

CAS	Component	Percent
64742-16-1	Petroleum Resin	Proprietary
64742-65-0	Distillates (Petroleum), Solvent-Dewaxed Heavy Paraffinic	Proprietary
6683-19-8	Inhibitor	0.10

### \*\*\*Section 4 - FIRST-AID MEASURES\*\*\*

## Description of Necessary Measures

### Inhalation

If adverse effects occur, remove to uncontaminated area. Give artificial respiration if not breathing. Get immediate medical attention.

### Skin Contact

Wash skin with soap and water for at least 15 minutes while removing contaminated clothing and shoes. Get immediate medical attention, if needed. Thoroughly clean and dry contaminated clothing before reuse.

### Eye Contact

Flush eyes with plenty of water for at least 15 minutes. Then get immediate medical attention.

### Ingestion

Get medical attention, if needed.

## Most Important Symptoms/Effects

### Acute

Mild skin irritation.

### Delayed

No information on significant adverse effects.

## Indication of Immediate Medical Attention and Special Treatment Needed, If Needed

Provide general supportive measures and treat symptomatically.

## Safety Data Sheet

Material Name: Hydrocarbon Resin  
NEVTAC® LT Resin

### \*\*\*Section 5 - FIRE-FIGHTING MEASURES\*\*\*

#### Suitable Extinguishing Media

Dry chemical, carbon dioxide, foam, water spray

#### Unsuitable Extinguishing Media

Do not use high-pressure water streams.

#### Special Hazard Arising from the Chemical

Avoid generating vapors; vapors dispersed in air in sufficient concentrations, and in the presence of an ignition source is a potential explosion hazard. Vapors are heavier than air and can collect in low areas; vapors can travel to an ignition source and flash back

**Combustion:** Upon combustion, this product emits carbon monoxide, carbon dioxide and/or low molecular weight hydrocarbons.

#### Fire Fighting Measures

Keep away from sources of ignition. Avoid inhalation of material or combustion by-products. Move material from fire area if it can be done without risk. Use extinguishing agents appropriate for surrounding fire. Dike for later disposal. Stay upwind and keep out of low areas.

#### Special Protective Equipment and Precautions for Firefighters

Wear full protective fire fighting gear including self contained breathing apparatus (SCBA) for protection against possible exposure.

### \*\*\*Section 6 - ACCIDENTAL RELEASE MEASURES\*\*\*

#### Personal Precautions, Protective Equipment and Emergency Procedures

Wear appropriate personal protective equipment. Keep unnecessary people away, isolate hazard area and deny entry. Avoid contact with skin and eyes. Avoid release to the environment. Only personnel trained for the hazards of this material should perform clean up and disposal.

#### Methods and Materials for Containment and Cleaning Up

Use non-sparking tools and equipment. Keep unnecessary people away, isolate hazard area and deny entry. Absorb with sand or other non-combustible material. Keep out of water supplies, sewers and soil. Collect spilled material in appropriate container for disposal. In case of spillage, stop the flow of material and block any potential routes to water systems.

### \*\*\*Section 7 - HANDLING AND STORAGE\*\*\*

#### Precautions for Safe Handling

Keep away from heat, sparks, open flame, and hot surfaces - No smoking. Wear protective gloves and eye/face protection. Keep away from all ignition sources. Avoid contact with skin and eyes. Always wear recommended personal protective equipment. Wear personal protective clothing and equipment, see Section 8. Take precautionary measures against static discharge. Dissipate static electricity during transfer by earthing (grounding and bonding) containers and equipment. Do not breathe vapor or mist.

# Safety Data Sheet

Material Name: Hydrocarbon Resin  
NEVTAC® LT Resin

## Conditions for Safe Storage, including any Incompatibilities

Store in a cool, dry place. Store in a well-ventilated area. Avoid contact with molten material. Keep separated from incompatible substances. Keep container tightly closed. Empty containers may contain product residue. Do not reuse empty containers without commercial cleaning or reconditioning. Store and handle in accordance with all current regulations and standards.

**Incompatibilities:** strong oxidizing materials

## \* \* \*Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION\* \* \*

### Component Exposure Limits

None

### Appropriate Engineering Controls

Provide a local exhaust ventilation system. Ventilation equipment should be explosion-resistant if explosive concentrations of material are present. It is recommended that all vapor control equipment such as local exhaust ventilation and material transport systems involved in handling of these product contain explosion relief vents or an explosion suppression system or an oxygen-deficient environment. Ensure that vapor-handling systems (such as exhaust ducts, vessels, and processing equipment) are designed in a manner to prevent the escape of vapors into the work area (i.e., there is no leakage from the equipment). Use only appropriately classified electrical equipment and powered industrial trucks.

### Individual Protection Measures, such as Personal Protective Equipment

#### Eyes/Face Protection

Wear splash resistant safety goggles with a face shield.

#### Skin Protection

Wear appropriate chemical resistant clothing.

#### Glove Recommendations

Wear appropriate chemical resistant gloves.

#### Respiratory Protection

A NIOSH approved respirator with organic vapor cartridges and N95 filters may be permissible under certain circumstances where airborne concentrations are expected to exceed exposure limits, or when symptoms have been observed that are indicative of overexposure.

## Safety Data Sheet

Material Name: Hydrocarbon Resin  
NEVTAC® LT Resin

### \*\*\*Section 9 - PHYSICAL AND CHEMICAL PROPERTIES\*\*\*

<b>Physical State:</b>	Viscous Liquid	<b>Vapor Density (air = 1):</b>	>1
<b>Appearance/ Color:</b>	Amber	<b>Evaporation Rate (water=1):</b>	< 1
<b>Odor:</b>	Mild petroleum odor	<b>pH:</b>	Not available
<b>Odor Threshold:</b>	Not available	<b>Boiling Point:</b>	>393°C.
<b>R&amp;B Softening Point, °C.:</b>	8 ± 3°C.	<b>Boiling Point Range:</b>	Not available
<b>Melting Point:</b>	Not available	<b>Vapor Pressure:</b>	Not available
<b>Freezing Point:</b>	Not available	<b>Decomposition Temperature:</b>	Not available
<b>Specific Gravity (water = 1):</b>	Approx. 0.902 @ 25°C	<b>KOC:</b>	Not available
<b>Molecular Weight (Mn):</b>	850	<b>Log KOW:</b>	Not available
<b>(Mw):</b>	1,400	<b>Water Solubility:</b>	Not available
<b>VOC:</b>	Not available	<b>Coeff. Water/Oil Dist:</b>	Not available
<b>Flash Point:</b>	500°F. COC ( 260°C.)	<b>Relative Density:</b>	Not available
<b>OSHA Flammability Class:</b>	Combustible Liquid	<b>Brookfield Viscosity, cps :</b>	@30°C. = 19,500 to 34,500
<b>Minimum Explosive Concentration:</b>	N/A	<b>Taste:</b>	Not available
<b>KSt-value (bar x m/s):</b>	N/A	<b>LEL:</b>	Not available
<b>Auto Ignition Temperature:</b>	>300°C.	<b>UEL:</b>	Not available

### \*\*\*Section 10 - STABILITY AND REACTIVITY\*\*\*

#### Reactivity

None known.

#### Chemical Stability

Stable at normal temperatures and pressure.

#### Possibility of Hazardous Reactions

Hazardous polymerization will not occur.

#### Conditions to Avoid

Avoid heat, flames, sparks and other sources of ignition. Avoid contact with incompatible materials. Avoid generating dust. Avoid contact with molten material.

#### Incompatible Materials

strong oxidizing materials

#### Hazardous Decomposition Products

Upon decomposition, this product emits carbon monoxide, carbon dioxide and/or low molecular weight hydrocarbons.

**Combustion:** oxides of carbon, carbon monoxide, hydrocarbons.

# Safety Data Sheet

Material Name: Hydrocarbon Resin  
NEVTAC® LT Resin

## \*\*\*Section 11 - TOXICOLOGICAL INFORMATION\*\*\*

### Acute and Chronic Toxicity

#### Component Analysis - LD50/LC50

The components of this material have been reviewed in various sources and the following selected endpoints are published: None

### Information on Likely Routes of Exposure

#### Inhalation

Exposure to aerosols or particulates from heated material may cause adverse lung effects if high concentrations are inhaled.

#### Ingestion

Ingestion may cause gastrointestinal irritation and diarrhea.

#### Skin Contact

No known significant effects or critical hazards. Prolonged or repeated contact can defat the skin and lead to irritation, cracking and/or dermatitis. Heated material can cause thermal burns.

#### Eye Contact

May cause slight transient irritation. Heated material can cause thermal burns.

#### Immediate Effects

No known significant effects or critical hazards.

#### Delayed Effects

No known significant effects or critical hazards.

#### Medical Conditions Aggravated by Exposure

No data available.

#### Irritation/Corrosivity Data

No information available for the product.

#### Respiratory Sensitization

No information available for the product.

#### Dermal Sensitization

No information available for the product.

#### Germ Cell Mutagenicity

No information available for product.

# Safety Data Sheet

Material Name: Hydrocarbon Resin  
NEVTAC® LT Resin

## Component Carcinogenicity

No information available for product

### Component: CAS # 64742-65-0

This additive is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA. Meets EU requirement of less than 3% (w/w) DMSO extract for total polycyclic aromatic compound (PAC) using IP 346.

## Reproductive Toxicity

No information available for product.

## Specific Target Organ Toxicity - Single Exposure

No information available for the product.

## Specific Target Organ Toxicity - Repeated Exposure

No information available for the product.

## Aspiration Hazard

No information available for the product.

<b>***Section 12 - ECOLOGICAL INFORMATION***</b>
--

## Ecotoxicity

No information available for the product. Not expected to be harmful to aquatic organisms.

## Component Analysis - Aquatic Toxicity

No information available for the product.

## Persistence and Degradability

No information available for the product. This product is unlikely to biodegrade at a significant rate.

## Bioaccumulation

No information available for the product. Likely to have some potential to bioaccumulate

## Mobility in Soil

No information available for the product.

## Other Adverse Effects:

No known significant effects or critical hazards. No other adverse environmental effects are expected from this product.

## Safety Data Sheet

Material Name: Hydrocarbon Resin  
NEVTAC® LT Resin

### \*\*\*Section 13 - DISPOSAL CONSIDERATIONS\*\*\*

#### Disposal Methods

Dispose in accordance with all applicable regulations. Regulations vary. Consult local authorities before disposal.

#### Disposal of Contaminated Packaging

Dispose of waste material according to Local, State, Federal, and Provincial Environmental Regulations.

### \*\*\*Section 14 - TRANSPORT INFORMATION\*\*\*

#### US DOT Information

**Shipping Name:** Elevated temperature liquid, n.o.s. at or above 100 °C and below its flash point including molten metals, molten salts, etc. (Contains: Petroleum Hydrocarbon Resin)

**UN/NA #: 3257 Hazard Class: 9 Packing Group: III**

**Required Label(s): 9**

Not DOT Hazardous in non-bulk packaging (Drums / Pails)

#### TDG Information

**Shipping Name:** Elevated temperature liquid, n.o.s. at or above 100 °C and below its flash point including molten metals, molten salts, etc. (Contains: Petroleum Hydrocarbon Resin)

**UN #: 3257 Hazard Class: 9 Packing Group: III**

**Required Label(s): 9**

Not Hazardous in non-bulk packaging (Drums / Pails)

### \*\*\*Section 15 - REGULATORY INFORMATION\*\*\*

#### U.S. Federal Regulations

None of this product's components are listed under SARA Section 302 (40 CFR 355 Appendix A), SARA Section 311/312 (40 CFR 370.21), SARA Section 313 (40 CFR 372.65), CERCLA (40 CFR 302.4), TSCA 12(b), or require an OSHA process safety plan.

#### SARA 311/312 Hazardous categories

Acute Health: No

Chronic Health: No

Fire: No

Pressure: No

Reactive: No



## Safety Data Sheet

Material Name: Hydrocarbon Resin  
NEVTAC® LT Resin

### U.S. State Regulations

The following components appear on one or more of the following state hazardous substances lists: **None**

Component	CAS	CA	MA	MN	NJ	PA
Distillates (Petroleum), Solvent-Dewaxed Heavy Paraffinic	64742-65-0	No	No	No	No	No

### Not regulated under California Proposition 65

### Canada Regulations

This product has been classified in accordance with the criteria of the Controlled Products Regulations (CPR) and the SDS contains all of the information required by the CPR.

### Canadian WHMIS Ingredient Disclosure List (IDL)

None of the components of this material is on Canadian WHMIS Ingredient Disclosure List.

### Canadian WHMIS Information

Not classified.

### Component Analysis – Inventory

Component	CAS	US	CA	EU	AU	PH	JP	KR	CN	NZ
Petroleum Resin	64742-16-1	Yes	DSL	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Distillates (Petroleum), Solvent-Dewaxed Heavy Paraffinic	64742-65-0	Yes	DSL	EIN	Yes	Yes	No	Yes	Yes	Yes
Inhibitor	6683-19-8	Yes	DSL	EIN	Yes	Yes	Yes	Yes	Yes	Yes

CAS #6683-19-8: Benzenepropanoic acid, 3,5-bis(1,1-dimethylethyl)-4-hydroxy-, 2,2- bis[[3-[3,5-bis(1,1-dimethylethyl)-4-hydroxyphenyl]-1- oxopropoxy]methyl] -1,3-propanediyl ester

## Safety Data Sheet

Material Name: Hydrocarbon Resin  
NEVTAC® LT Resin

### \*\*\*Section 16 - OTHER INFORMATION\*\*\*

**NFPA Ratings: Health: 1 Fire: 1 Reactivity: 0**

Hazard Scale: 0 = Minimal 1 = Slight 2 = Moderate 3 = Serious 4 = Severe

#### **HMIS RATINGS:**

**Health: 1**

**Fire: 1**

**Reactivity: 0**

**Pers. Prot.: B Minimum**

Hazard Scale: 0 = Minimal 1 = Slight 2 = Moderate 3 = Serious 4 = Severe \* = Chronic hazard

#### **Key / Legend**

ACGIH - American Conference of Governmental Industrial Hygienists; ADR - European Road Transport; AU - Australia; BOD - Biochemical Oxygen Demand; C - Celsius; CA - Canada; CAS - Chemical Abstracts Service; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CN - China; CPR - Controlled Products Regulations; DFG - Deutsche Forschungsgemeinschaft; DOT - Department of Transportation; DSL - Domestic Substances List; EEC - European Economic Community; EINECS - European Inventory of Existing Commercial Chemical Substances; EPA - Environmental Protection Agency; EU - European Union; F - Fahrenheit; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; ICAO - International Civil Aviation Organization; IDL - Ingredient Disclosure List; IMDG - International Maritime Dangerous Goods; JP - Japan; Kow - Octanol/water partition coefficient; KR - Korea; LEL - Lower Explosive Limit; LOLI - List Of Lists MAK - Maximum Concentration Value in the Workplace; MEL - Maximum Exposure Limits; NFPA - National Fire Protection Agency; NIOSH - National Institute for Occupational Safety and Health; NJTSR - New Jersey Trade Secret Registry; NTP - National Toxicology Program; NZ - New Zealand; OSHA - Occupational Safety and Health Administration; PH - Philippines; RCRA - Resource Conservation and Recovery Act; RID - European Rail Transport; RTECS - Registry of Toxic Effects of Chemical Substances®; SARA - Superfund Amendments and Reauthorization Act; STEL - Short-term Exposure Limit; TDG - Transportation of Dangerous Goods; TSCA - Toxic Substances Control Act; TWA - Time Weighted Average; UEL - Upper Explosive Limit; US - United States

#### **Other Information**

Reasonable care has been taken in the preparation of this information; however, the manufacturer makes no warranty whatsoever including the warranty of merchantability, expressed or implied, with respect to this information.